Form Approved REPORT DOCUMENTATION PAGE OMB No. 0704-0188 Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate of any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headquarters Service, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Affington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS. 3. DATES COVERED (From - To) 1. REPORT DATE (DD-MM-YYYY) 2. REPORT TYPE 08/01/1998-12/31/2000 1/8/2002 Final Report 5a. CONTRACT NUMBERS 4. TITLE AND SUBTITLE Observation and Modeling of Spatial Wave Coherence 5b. GRANT NUMBER N00014-98-1-0793 5c. PROGRAM ELEMENT NUMBER **5d. PROJECT NUMBER** 6. AUTHOR(S) Drs. Eugene A. Terray and Mark A. Donelan 5e. TASK NUMBER 5f. WORK UNIT NUMBER 8. PERFORMING ORGANIZATION REPORT 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) NUMBER Woods Hole Oceanographic Institution Applied Ocean Physics and Engineering Department 98 Water Street, MS #12 Woods Hole, Massachusetts 02543-1053 10. SPONSORING/MONITORING ACRONYM(S) 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Office of Naval Research Code 321CD 11. SPONSORING/MONITORING AGENCY Ballston Centre Tower One REPORT NUMBER 800 N. Quincy Street Arlington, VA 22217-5660 12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited 13. SUPPLEMENTARY NOTES 14. ABSTRACT The work reported here was undertaken as part of the Mobile Offshore Base (MOB) study. We used field observations taken from a

fixed tower using arrays of surface elevation gages to estimate the along-crest coherence of wind generated water waves. The coherence scale was found to depend linearly on wavenumber.

15. SUBJECT TERMS Wind waves, Spatial coherence, Crest length statistics 20020805 094

16. SECURITY CLASSIFICATION OF: a. REPORT b. ABSTRACT c. THIS PAGE			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
Unclassified	Unclassified	Unclassified	Unlimited	3	19 b. TELEPHONE NUMBER (Include are code)

Final Report OBSERVATION AND MODELING OF SPATIAL WAVE COHERENCE

E.A. Terray

Department of Applied Ocean Physics and Engineering

MS-11, 217 Bigelow

Woods Hole Oceanographic Institution

Woods Hole, MA 02543

(508) 289-2438 (Voice), (508) 457-2194 (Fax)

eterray@whoi.edu

M.A. Donelan
Rosenstiel School of Marine and Atmospheric Sciences
University of Miami
4600 Rickenbacker Causeway
Miami, FL 33149
(305) 361-4717 (voice)
mdonelan@rsmas.miami.edu

Award Number: N00014-98-0793

GOALS AND OBJECTIVES

The Mobile Offshore Base (MOB) program was tasked with addressing the feasibility of building large floating structures, with scales of order a kilometer, that would serve as forward supply and staging facilities in support of remote naval operations. An important design issue for a structure of this size is the coherence of the forcing by long-period ocean waves. The study reported here is a component of the MOB program aimed at developing an improved understanding of the along-crest coherence and group statistics of long period waves. The specific objectives of this work are to provide:

- statistics of crest lengths and "runs" of high waves
- estimates of the array covariance $\langle \eta(x,y,t)\eta(0,0,0)\rangle$
- software for time-frequency analysis of wave measurements
- software for the time-frequency synthesis of wave fields.

APPROACH

We investigated these issues using data collected by one of the co-PIs using an extended 14-element array, and a compact 6-element array of capacitance wavestaffs deployed from a tower in a large lake (Donelan *et al.*, 1986, 2000). The fetch at this site varied from 1 to roughly 300 km, thus providing a wide range of wave development. Our proposed analysis was based on the "Wavelet Decomposition Method" (WDM) of Donelan *et al.* (1996), which permits the identification of individual waves of a given scale and direction passing through the array at each instant of time.

RESULTS

[1] The estimator proposed by Donelan *et al.* (1996) is based on the assumption that the directional spread of individual wavetrains is much smaller that the statistical spread of the wave field as a whole, and that only a single wavetrain (which itself may be composed of waves of many scales) is incident on the array at any instant. We have relaxed this constraint to permit several wavetrains to be present at once. The new estimator reduces to that of Donelan *et al.* (1996) for a single wave and infinite signal-to-noise ratio. Applying it to data suggests that their assumption is satisfied roughly 90% of the time.

[2] We have studied "crest lengths" (i.e. the along-crest correlation of high waves) in two ways. In the first, we use both the WDM and conventional Fourier transform techniques to estimate the temporally-averaged lateral correlation of the waves. A typical example using data from the large 14-element array is given in Figure 1. In the second approach we introduce a model of the lateral crest profile, which we take to be approximately Gaussian, so that

$$\eta(y) = \eta_o e^{-(\beta y)^2} ,$$

where the waves are assumed to be propagating in the x-direction, and the parameter β is a measure of the lateral sharpness of the crest. Wavelet decomposition was applied to data from the compact array (Donelan *et al.*, 2000) in order to identify the propagation directions of packets of waves, and assess their crest lengths by comparison of observed amplitudes across the propagation direction. Figure 2 shows that the dependence of β on the mean wavenumber of the crests in various frequency bands is approximately linear. In this case $\beta = 0.55 k$, and therefore the total average width of the crests to the half amplitude point is about half the wavelength. We were not successful in applying this approach to the extended array because of its sparseness.




Figure 1. Lateral correlation function computed using wavelets (o) and Fourier transform techniques (x) for data from the 14-gage array. The center frequency was 0.35Hz.




Figure 2. Dependence of the lateral crest shape parameter on the wavenumber of the waves for a case of wind waves at short fetch using data from the compact array.

REFERENCES

Donelan, M.A. J. Hamilton, and W.H. Hui (1986): Directional spectra of wind-generated waves. *Phil. Trans. Roy. Soc.*, **A315**, 509-562.

Donelan, M.A., W.M. Drennan and A.K. Magnusson (1996): Nonstationary analysis of the directional properties of propagating waves. *J. Phys. Oceanogr.*, **26**(9), 1901-1914.

SUPPORTED PUBLICATIONS AND PRESENTATIONS

Donelan, M.A., W.M. Drennan and E.A. Terray (2000): Wavenumber spectra of wind waves in the range of 1m to 50m. *The Wind--Driven Air-Sea Interface: Electromagnetic and Acoustic Sensing, Wave Dynamics and Turbulent Fluxes*, M. Banner (ed.), School of Mathematics, The University of New South Wales, Sydney, Australia, pp. 35-42.

Donelan, M.A. (2000): Wave propagation and wind-wave interaction. Abstract and presentation at the NCAR Geophysical Turbulence Program Workshop: *Turbulence and the Air-Sea Interface*. Boulder, Colorado, August 15-17, 2000.

Additional manuscripts are in preparation.